



2025 Annual Groundwater Monitoring and Corrective Action Report

*Former LOS Ponds 2 and 3 Multiunit
Leland Olds Station
Stanton, North Dakota*



Prepared for
Basin Electric Power Cooperative


Prepared by
Barr Engineering Co.

January 2026

4585 Coleman Street, Suite 210
Bismarck, ND 58503
701.255.5460

barr.com





January 2026

1	Executive Summary	1
2	Introduction	2
2.1	Physical Setting.....	2
2.2	Purpose	3
2.3	CCR Rule Requirements.....	3
3	Groundwater Monitoring Program.....	5
3.1	Groundwater Monitoring System.....	5
3.1.1	Changes to Groundwater Monitoring System.....	5
3.2	Actions Completed/Problems Encountered	6
3.3	Data and Collection Summary	6
3.3.1	May 2025 Detection Monitoring Event.....	6
3.3.2	August 2025 Detection Monitoring Event	6
3.4	Activities for Upcoming Year	6
4	References	7



Tables

Table 1	CCR Rule Requirements and Compliance	3
Table 2	Groundwater Monitoring System	5

Figures

Figure 1	Site Location
Figure 2	Monitoring Network
Figure 3	Spring 2025 Potentiometric Surface
Figure 4	Fall 2025 Potentiometric Surface

Attached Tables

Attached Table 1	Sampling Summary
Attached Table 2	Statistical Evaluation Summary
Attached Table 3	Water Quality Analytical Data Summary

Appendices

Appendix A	Lab and Field Reports
Appendix B	Groundwater Flow Rate



Abbreviations

asml	above mean sea level
ASD	Alternative Source Demonstration
bgs	below ground surface
CCR	Coal Combustion Residuals
CFR	Code of Federal Regulations
cm	Centimeter
EPA	Environmental Protection Agency
FGD	Flue gas desulfurization
ft	feet
LOS	Leland Olds Station
NDAC	North Dakota Administrative Code
NDDEQ	North Dakota Department of Environmental Quality
NPDES	National pollution discharge and elimination system
SAP	Sampling and Analysis Plan
sec	Second
SSI	Statistically Significant Increase
TDS	Total Dissolved Solids

1 Executive Summary

This 2025 Annual Groundwater Monitoring and Corrective Action Report (Annual Report) describes the monitoring program and results for the former Ponds 2 and 3 Multiunit (Multiunit) at Basin Electric Power Cooperative's (Basin Electric) Leland Olds Station (LOS; Site). The content of this report is to satisfy the requirements of the federal CCR rule.

At the beginning, end, and throughout 2025, the Multiunit was operating under a detection monitoring program as described in 40 CFR § 257.94 and NDAC 33.1-20-08-06-04. This program includes semi-annual detection monitoring events conducted in the spring and fall.

Pursuant to § 257.94 and NDAC 33.1-20-08-06-04, no statistically significant increases (SSIs) were determined for the May 2025 and August 2025 sampling events. Therefore, no assessment monitoring program (§ 257.95 and NDAC 33.1-20-08-06-04) or related corrective or remedial measures (§§ 257.96, 257.97, and 257.98; NDAC 33.1-20-08-06-06, -07, and -08) were necessary.

2 Introduction

Basin Electric Power Cooperative (Basin Electric) owns Leland Olds Station (LOS), a coal-fired generating station with two power-generating units, located southeast of Stanton, Mercer County, North Dakota (Figure 1). Unit 1 coal-based operations began in 1966, and Unit 2 operations began in 1975. Coal combustion residuals (CCR) were directed to four surface impoundments (Pond 1, Pond 2, Pond 3, and Pond 4) on the southeast side of the property. CCR produced at LOS includes fly ash, bottom ash, and flue gas desulfurization (FGD) waste.

Ponds 1 and 4 were closed-in-place in the mid-1990s. Bottom ash Ponds 2 and 3 (Multiunit or Site) continued operating until 2015. Pond 2 flowed into Pond 3, which discharged through Outfall 003 in accordance with the National Pollution Discharge Elimination System (NPDES) permit. In 2015, LOS converted to dry handling of bottom ash, and the Multiunit ceased accepting CCRs.

Closure of the southern half of Pond 2 was completed in 2017. Closure of the remaining portion of Pond 2 and all of Pond 3 began in 2019 and was completed in 2020. In compliance with the CCR Rule, a closure notification including certification by a qualified professional engineer that the closure was completed in accordance with the written closure plan and the requirements of Chapter 40 Code of Federal Regulations (CFR) § 257.102, was posted on October 26, 2020. The Multiunit is now closed-in-place.

This Annual Report describes the monitoring program and results for the Multiunit at the Site. No corrective actions were required or conducted in 2025.

Basin Electric utilizes a consulting firm, Barr Engineering Co. (Barr), to assist in groundwater reporting and analysis. Barr is familiar with the site and has reviewed the historical groundwater data and CCR information for the site and is knowledgeable about facility design and operation.

Additional Site monitoring information, including CCR reports and certifications, can be found on Basin Electric's CCR website: [Pond 2 Surface Impoundment - LOS - Basin Electric Power Cooperative](#) and [Pond 3 Surface Impoundment - LOS - Basin Electric Power Cooperative](#).

2.1 Physical Setting

The Multiunit is situated in the valley of the Missouri River. The valley floor is relatively flat, with two poorly defined terraces ranging from 1,670 feet above mean sea level (ft amsl) to a maximum elevation of 1,715 ft amsl near the southern property boundary. Seven of the CCR monitoring system monitoring wells (MW-2017-1 through MW-2017-4, MW-2017-7, MW-2017-10 and MW-2017-11) are located on the lower (first) terrace level, while one is located on the upper (second) terrace (MW-2017-8).

The geology underlying the Multiunit is generally comprised of more than 50 feet of alluvial silt, silty sand, and gravel deposits. The upper terrace level appears to be underlain by at least 25 more feet of alluvial deposits than is found adjacent to the Multiunit. The alluvial deposits are underlain by the Sentinel Butte Formation, which is described as 1,000 feet or more of continental deposits consisting of dense clay, weakly cemented sandstone, and mudstone interlaced with occasional lignite beds that typically range from 5 to 10 feet in thickness.

Groundwater at the lower terrace locations is found within alluvial deposits comprised primarily of silty, fine to medium-grained sand at depths ranging from approximately 17 to 35 feet below ground surface (ft bgs). Aquifer testing completed at monitoring wells MW-2017-3, MW-2017-4, MW-2017-5, and MW-2017-

6 indicates hydraulic conductivity values within the monitored aquifer range from 1.28×10^{-2} to 6.94×10^{-4} centimeters per second (cm/sec) with a geometric mean of approximately 2.0×10^{-3} cm/sec (5.67 feet per day [ft/day]) (AECOM, April 2019).

The potentiometric surface of the uppermost groundwater underlying the lower terrace area is typically encountered at elevations between 1,658 and 1,662 ft amsl, depending on the stage of the adjacent Missouri River. The stage of the Missouri River was 1659.07 ft amsl during the spring sampling event and 1659.20 ft amsl during the fall sampling event. Although the direction of groundwater flow is highly influenced by changes in the elevation of the Missouri River, the net flow direction is expected to be eastward in the general direction of river flow, with some flow northward into the river. Groundwater at the upper terrace is perched at a considerably higher elevation with limited hydraulic connection to the lower terrace. As a result, the groundwater from the upper terrace is expected to act as a limited background/upgradient influence on the uppermost aquifer at the Multiunit.

Additional Site information can be found on Basin Electric's CCR website in the Pond 2 and Pond 3 Multiunit CCR Groundwater Monitoring System Report (AECOM, June 2022).

2.2 Purpose

As stated in § 257.90(e) and NDAC 33.1-20-08-06-01(e), the Annual Report must:

- Document the status of groundwater monitoring and any corrective action programs for the CCR unit,
- Summarize key actions completed,
- Describe any problems encountered,
- Discuss actions to resolve the problems, and
- Project key activities for the upcoming year.

2.3 CCR Rule Requirements

Additional requirements for the Annual Report, as outlined in § 257.90(e) and NDAC 33.1-20-08-06-01(e), and this Site's compliance with the CCR Rules, are summarized in Table 1.

Table 1 CCR Rule Requirements and Compliance

EPA CCR Rule Reference (40 CFR)	NDDEQ CCR Rule Reference (NDAC)	Content Required in Report	Location
§ 257.90(e)(1)	§ 33.1-20-08-06-01(e)(1)	Monitoring System Figure: A map, aerial image, or diagram showing the CCR unit and all background (or upgradient) and downgradient monitoring wells, to include the well identification numbers, that are part of the groundwater monitoring program for the CCR unit.	Section 3.1 Groundwater Monitoring System; see Figure 1

EPA CCR Rule Reference (40 CFR)	NDDEQ CCR Rule Reference (NDAC)	Content Required in Report	Location
§ 257.90(e)(2)	§ 33.1-20-08-06-01(e)(2)	Monitoring System Adjustments: Identification of any monitoring wells that were installed or decommissioned during the preceding year, along with a narrative description of why those actions were taken.	Section 3.1.1 Changes to Groundwater Monitoring System
§ 257.90(e)(3)	§ 33.1-20-08-06-01(e)(3)	Data and Collection Summary: In addition to all the monitoring data obtained under §257.90 through §257.98 and §33.1-20-08-06, a summary including the number of groundwater samples that were collected, and whether the sample was required by the detection monitoring or assessment monitoring programs.	Section 3.3 Data and Collection Summary; monitoring data included in Attached Table 1, Attached Table 2, Attached Table 3, Appendix A, and Appendix B
§ 257.90(e)(4)	§ 33.1-20-08-06-01(e)(4)	Monitoring Program: A narrative discussion of any transition between monitoring programs (e.g., the date and circumstances for transitioning from detection monitoring to assessment monitoring in addition to identifying the constituent(s) detected at a statistically significant increase over background levels).	Not applicable – No transition between monitoring programs was necessary
§ 257.90(e)(5)	§ 33.1-20-08-06-01(e)(5)	Other Information: Other information required, if applicable, to be included in the annual report as specified in §257.90 through §257.98 and §33.1-20-08-06.	No changes to the groundwater monitoring system occurred in 2025. The system described in Section 2.1 and shown on Figure 2 supplanted the groundwater monitoring system described in the Groundwater Monitoring System Certification (AECOM, April 2019). Actions Completed/Problems Encountered
§ 257.90(e)(6)	<u>N/A</u>	Executive Summary: A section at the beginning of the annual report that provides an overview of the current status of groundwater monitoring and corrective action programs for the CCR unit.	Executive Summary

3 Groundwater Monitoring Program

This section documents the status of the groundwater monitoring and corrective action program for the Multiunit in 2025. A description of the groundwater monitoring system is included in Section 3.1, key actions completed and problems encountered are described in Section 2.2, the monitoring and analytical results are described in Section 3.3, and key activities planned for 2026 are described in Section 3.4.

3.1 Groundwater Monitoring System

The certified groundwater monitoring well network around the Multiunit consists of two background wells and six downgradient wells, sampled for groundwater analysis on a semi-annual basis. Background wells monitor water quality that is not potentially influenced by the presence of CCR in the Multiunit. Well locations are described below in Table 2 and shown in Figure 2.

Table 2 Groundwater Monitoring System

CCR Unit	Background Wells	Downgradient Wells
Ponds 2 and 3 Multiunit	MW-2017-1 and MW-2017-8	MW-2017-2, MW-2017-3, MW-2017-4, MW-2017-7, MW-2017-10, and MW-2017-11

Several wells are not included in the compliance network as they are used for characterization, including MW-2017-8D and MW-2017-9. MW-2017-8D is screened in bedrock.

Two monitoring wells, MW-2017-5 and MW-2017-6, have been excluded from the groundwater monitoring network due to concerns about their installation, specifically the improper placement of the annular seal and the grout in contact with groundwater. The wells remain in place for optional collection of groundwater level measurements for potential inclusion in the potentiometric evaluation of the Site.

Baseline monitoring initiated in September 2017 for wells in the monitoring network (except MW-2017-10 and MW-2017-11 as described below) and included sampling groundwater over eight baseline monitoring events. The results of baseline monitoring are discussed in previous Annual Reports.

Detection monitoring events in 2025 and prior to 2025 were performed in general accordance with procedures established in the site-specific Sampling and Analysis Plan (SAP) (AECOM, June 2022), which is included in the facility's Operating Record. The Multiunit was placed in Detection monitoring in April 2019, with the first Detection monitoring groundwater sampling event completed in November 2019. Detection monitoring events have been completed semi-annually since November 2019. The results of prior Detection monitoring events were presented and discussed in the previously published Annual Reports, which can be found on Basin Electric's CCR website.

3.1.1 Changes to Groundwater Monitoring System

No changes to the groundwater monitoring system occurred in 2025. The system described in Section 3.1 and shown in Figure 2 supplanted the groundwater monitoring system described in the Groundwater Monitoring System Certification (AECOM, April 2019).

3.2 Actions Completed/Problems Encountered

The following actions were completed in 2025:

- **Detection Monitoring Sampling:** Groundwater samples were collected from each well in the groundwater monitoring system on May 6-7, 2025, and August 4-5, 2025. Groundwater samples were analyzed for Appendix III constituents, per the detection monitoring program of the CCR Rules (§ 257.94 and NDAC 33.1-20-08-06-04) (Attached Table 1).
- **SSI Evaluation:** SSI evaluations were conducted in accordance with the Groundwater Statistical Method Selection Certification (AECOM, 2019) for the May 2025 and August 2025 detection monitoring events. There were no SSIs from either event. (Attached Table 2)

No problems were encountered in 2025.

3.3 Data and Collection Summary

3.3.1 May 2025 Detection Monitoring Event

Groundwater samples were collected from the nine groundwater monitoring network wells at the Site on May 6-7, 2025. No SSIs were identified. A summary of results is included in Attached Table 3. Field data sheets and analytical laboratory reports for detection monitoring sampling are included in Appendix A. Water level contours are shown on Figure 3, and flow calculations are included in Appendix B.

3.3.2 August 2025 Detection Monitoring Event

Groundwater samples were collected from the nine groundwater monitoring network wells at the Site on August 4-5, 2025. No SSIs were identified. A summary of results is included in Attached Table 3. Field data sheets and analytical laboratory reports for detection, monitoring, and sampling are included in Appendix A. Water level contours are shown in Figure 4, and flow calculations are included in Appendix B.

3.4 Activities for Upcoming Year

The following key activities for analytical results and statistical evaluations are planned for 2025:

- Evaluate analytical results from 2026 semi-annual detection monitoring events for SSIs according to the Statistical Certification (AECOM, April 2019).
- Review the conceptual site model and consider recommendations for improvements to the monitoring well network if needed.

4 References

- AECOM. (April 2019). *Pond 2 and Pond 3 Multiunit CCR Groundwater Monitoring System Report, Leland Olds Station. Prepared for Basin Electric Power Cooperative.* .
- AECOM. (June 2022). *Pond 2 and Pond 3 Multiunit Sampling and Analysis Plan, CCR Monitoring Program, Leland Olds Station. Prepared for Basin Electric Power Cooperative.* .



Attached Tables



Attached Table 1
Sampling Summary
2025 Annual Monitoring Report
BEPC-LOS Multiunit

Event Classification and Number	Monitoring Well	Up or Down Gradient	Event date	No. Samples
Detection Monitoring Event #1	MW-2017-1	Up		2
Detection Monitoring Event #1	MW-2017-2	Down		1
Detection Monitoring Event #1	MW-2017-3	Down		1
Detection Monitoring Event #1	MW-2017-4	Down		1
Detection Monitoring Event #1	MW-2017-7	Down		1
Detection Monitoring Event #1	MW-2017-8	Up		1
Detection Monitoring Event #1	MW-2017-10	Down		2
Detection Monitoring Event #1	MW-2017-11	Down		1
Detection Monitoring Event #2	MW-2017-1	Up		1
Detection Monitoring Event #2	MW-2017-2	Down		2
Detection Monitoring Event #2	MW-2017-3	Down		1
Detection Monitoring Event #2	MW-2017-4	Down		1
Detection Monitoring Event #2	MW-2017-7	Down		1
Detection Monitoring Event #2	MW-2017-8	Up		1
Detection Monitoring Event #2	MW-2017-10	Down		1
Detection Monitoring Event #2	MW-2017-11	Down		1

Attached Table 2
Statistical Evaluation Summary
2025 Annual Monitoring Report
LOS Multiunit CCR Groundwater Compliance

Spring 2025

Well	Appendix III Constituents						
	Boron (T)	Calcium (T)	Chloride	Fluoride	pH	Sulfate	TDS
MW-2017-2	1.5	78.8	11.3	0.48	7.3	271	711
MW-2017-3	1.51	111	11	0.5	7.2	156	882
MW-2017-4	1.2	151	10.8	0.78	7.1	298	886
MW-2017-7	2.23	72.2	11.4	1.21	7.5	224	721
MW-2017-10	0.88	96	10.8	0.86	7.4	284	726
MW-2017-11	1.3	66.6	11.2	0.76	7.4	169	606

Fall 2025

Well	Appendix III Constituents						
	Boron (T)	Calcium (T)	Chloride	Fluoride	pH	Sulfate	TDS
MW-2017-2	1.11	119	11.7	0.41	7.2	291	916
MW-2017-3	1.25	112	11.3	0.52	7.2	136	966
MW-2017-4	1.18	163	11.2	0.8	7.1	323	908
MW-2017-7	2.17	71.4	11.5	1.15	7.5	243	721
MW-2017-10	0.83	94.9	10.9	0.91	7.5	308	671
MW-2017-11	1.25	63.4	11.5	0.78	7.5	178	592

Sample had a value higher than the prediction limit determined from background data and is a verified SSI

Sample did not have a value higher than the prediction limit determined from background data

pH: two-sided prediction limit; color indicates sample higher and/or lower than prediction limits

Attached Table 3
Water Quality Analytical Data Summary
2025 Annual Monitoring Report
BEPC LOS Multiunit


Location			MW-2017-1	MW-2017-1	MW-2017-2	MW-2017-2	MW-2017-3	MW-2017-3	MW-2017-4	MW-2017-4	MW-2017-7		MW-2017-7	MW-2017-8	MW-2017-8	MW-2017-8D	MW-2017-8D	MW-2017-10	MW-2017-10	MW-2017-11	MW-2017-11	
Date			5/8/25	8/4/25	6/8/25	8/4/25	6/8/25	8/4/25	5/8/25	8/4/25	6/8/25		8/4/25	5/7/25	8/4/25	5/7/25	8/8/25	5/8/25	8/4/25	5/8/25	8/4/25	
Sample Type			N	N	N	N	N	N	N	N	N	FD	N	N	N	N	N	N	N	N	N	FD
Parameter	Analysis Location	Units																				
Appendix III																						
Boron, total	Lab	mg/l	0.54	0.44	1.60	1.11	1.51	1.25	1.20	1.18	2.23	2.32	2.17	0.44	0.43	0.69	0.67	0.89	0.83	1.30	1.25	1.24
Calcium, total	Lab	mg/l	217	231	78.8	119	111	112	151	163	72.2	74.5	71.4	128	127	8.50	8.30	96.0	94.8	66.6	63.4	62.0
Chloride	Lab	mg/l	14.7	16.4	11.3	11.7	11.0	11.3	10.8	11.2	11.4	11.4	11.5	26.5	26.2	16.6	16.2	10.8	10.9	11.2	11.5	11.5
Fluoride	Lab	mg/l	0.38	0.35	0.48	0.41	0.60	0.52	0.78	0.80	1.21	1.22	1.15	0.39	0.40	0.68	0.65	0.86	0.91	0.76	0.78	0.78
pH	Field	pH units	6.80	6.97	7.26	7.16	7.18	7.24	7.06	7.14	7.46	--	7.51	7.36	7.41	7.96	7.94	7.41	7.49	7.41	7.46	--
Solids, total dissolved	Lab	mg/l	1250	1230	711	916	882	988	888	908	721	741	721	3680	3620	1960	1930	726	671	606	592	585
Sulfate, as SO4	Lab	mg/l	355	326	271	291	156	136	298	323	224	261	243	1630	1740	346	384	284	308	169	178	180

-- Not analyzed/Not available.
N Sample Type: Normal
FD: Sample Type: Field Duplicate
U: The analyte was analyzed for, but was not detected.





Figures














Appendices





Appendix A

Lab and Field Reports



Well/Piezo ID:

MW-2017-1

Ground Water Sample Collection Record

Client: BEPC Date: 5/16/25
 Project No: Time: 0740
 Site Location: AVS LAS PLANT Finish: 0827
 Weather Conds: Collector(s) MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 29.75 c. Casing Material PVC Pump Settings 27/3 e. 100 PSI
 b. Water Table Depth 25.5 d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model
 YSI
 HACH

Serial Number
 5320084101
 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0802	INITIAL 4L	10.2	.40	1784	6.90	-41.4	4.85	clear	25.11
0806	5 L	10.1	.41	1784	6.90	-41.16	4.60	↓	25.10
0810	6 L	10.2	.49	1784	6.90	-42.3	4.20	↓	25.59
0814	7 L	10.2	.48	1784	6.90	-42.16	4.17	↓	25.10
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0817
	500mL	1	HNO3	Metals	↓

Comments

Signature Man

Date 5/16/25

Well/Piezo ID:

MIN-2017-2

Ground Water Sample Collection Record

Client: BEPC Date: 5/16/25
 Project No: Time: 0828
 Site Location: AVS LOS PLANT Finish: 0916
 Weather Conds: Cloudy, cool Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 34.15 c. Casing Material PVC Pump Settings 22/3 @ 100psi
 b. Water Table Depth 22.91 d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0849	INITIAL	10.1	.44	1051	7.25	-66.7	24.9	Rusty	22.95
0853	7 L	10.2	.54	1049	7.25	-68.7	19.6		22.95
0857	8 L	10.2	.68	1048	7.25	-71.5	19.5		22.95
0901	9 L	10.1	.66	1047	7.25	-70.9	18.4		22.96
0905	10 L	10.2	.62	1047	7.25	-71.4	16.7		22.95
0909	11 L	10.2	.60	1047	7.26	-72	16.6		22.95
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0911
	500mL	1	HNO3	Metals	

Comments

Signature M. M. M.

Date 5/16/25

Well/Piezo ID:

MW-2017 3

Ground Water Sample Collection Record

Client: BEPC Date: 5/6/25
 Project No: _____ Time: 0920
 Site Location: AVS LOS plant Finish: 0954
 Weather Conds: cloudy, cool Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 29.66 c. Casing Material PVC Pump Settings 27/30 100 psi
 b. Water Table Depth 24.78 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make _____ Model _____
 YSI
 HACH

Serial Number

5320084101

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0935	INITIAL 5L	10.2	3.30	1358	7.17	-103.0	9.4	clear	24.56
0939	6 L	10.3	3.08	1359	7.18	-103.5	10.3		24.55
0943	7 L	10.3	3.03	1362	7.18	-104.4	9.3		24.58
0947	8 L	10.3	3.05	1365	7.18	-102.7	8.5	↓	24.56
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0953
	500mL	1	HNO3	Metals	↓

Comments _____

Signature manDate 5/6/25

Well/Piezo ID:

MW-2017-4

Ground Water Sample Collection Record

Client: BEPC Date: 5/10/25
 Project No: Time: 1015
 Site Location: AVS LAS PLANT Finish: 1055
 Weather Conds: Sunny 50° Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 34.27 c. Casing Material PVC
 b. Water Table Depth 20.05 d. Casing Diameter
~~21.50~~

Pump Settings 27/3 @ 60psi

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model
 YSI
 HACH

Serial Number
 5320084101
 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
1031	INITIAL 5L	10.0	.29	1275	7.05	-52.3	34.7	orange	26.06
1035	6 L	10.5	.25	1267	7.03	-38.7	24.3	rusty	26.09
1039	7 L	10.5	.26	1269	7.04	-40.3	21.9		26.06
1043	8 L	10.5	.40	1288	7.04	-44.0	22.3		26.10
1047	9 L	10.5	.31	1291	7.05	-48.2	22.8	↓	26.11
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1048
	500mL	1	HNO3	Metals	↓

Comments

Signature man

Date 5/10/25

Well/Piezo ID:

MW-2017-10

Ground Water Sample Collection Record

Client: BEPC Date: 5/6/25
 Project No: Time: 1101
 Site Location: AVS LOS PLANT Finish: 1139
 Weather Conds: Sunny, 80, Breezy Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 44.100 c. Casing Material PVC Pump Settings 20/4 @ 50 psi
 b. Water Table Depth 34.08 d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
1118	INITIAL 4L	11.4	0.20	990	7.43	-74.1	4.87		34.15
1122	5 L	11.3	.15	989	7.42	-72.0	4.89		34.12
1126	10 L	11.4	.15	989	7.43	-67.8	3.46		34.16
1130	7 L	11.5	.13	989	7.41	-100	2.96		34.17
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1131
	500mL	1	HNO3	Metals	↓

Comments

Signature

Man

Date

5/6/25

Well/Piezo ID:

MW-2017-11

Ground Water Sample Collection Record

Client: BEPC Date: 5/10/25
 Project No: Time: 1224
 Site Location: AVS - LOS Plant Finish: 1302
 Weather Conds: Sunny breezy Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 49.92 c. Casing Material PVC Pump Settings 26/4 @ 50psi
 b. Water Table Depth 39.89 d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model
 YSI
 HACH

Serial Number

5320084101

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
1245	INITIAL 4L	11.3	.22	878	7.40	-65.2	1.28	clear	39.88
1249	5 L	11.2	.20	880	7.41	-68.4	1.85	↓	39.87
1253	10 L	11.3	.18	877	7.41	-70.8	1.45	↓	39.87
1257	7 L	11.3	.16	879	7.41	-72.9	.87	↓	39.88
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1259
	500mL	1	HNO3	Metals	↓

Comments

Signature Yman

Date 5/10/25

Well/Piezo ID:

MW-2017-7

Ground Water Sample Collection Record

Client: BEPC Date: 5/10/25
 Project No: _____ Time: 1315
 Site Location: AVS - LAS Plant Finish: 1355
 Weather Conds: Breezy, cloudy, cool Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒a. Total Well Length 45.3 c. Casing Material PVCPump Settings 20/4 e/opsb. Water Table Depth 39.96 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make _____ Model _____ Serial Number _____
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
1332	INITIAL 3L	11.0	1.4	1037	7.45	95.7	2.00	yellow	40.0
1336	4 L	11.1	1.28	1041	7.45	90.8	2.58	Brown	40.01
1340	5 L	11.2	1.26	1039	7.45	88.5	2.87		40.0
1344	10 L	11.2	1.22	1045	7.45	80.0	1.09	↓	40.02
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

DUP

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1345
	500mL	1	HNO3	Metals	↓

Comments _____

Signature manDate 5/10/25

Well/Piezo ID:

MW-2017-8

Ground Water Sample Collection Record

Client: BEPC Date: 5/7/25
 Project No: Time: 0750
 Site Location: AVS LAS PLANT Finish: 0833
 Weather Conds: Sunny cool Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 35.35 c. Casing Material PVC

Pump Settings 20/4 @ 40 PSI

b. Water Table Depth 29.30 d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0815	INITIAL 4L	9.1	.41	4833	7.38	-309.7	17.6	clear	29.3
0819	4.75 L	9.1	.39	4854	7.38	-312.9	17.7		29.31
0822	5.5 L	9.1	.37	4865	7.37	-308.3	16.6		29.3
0826	6.25 L	9.1	.37	4882	7.36	-305.3	15.9		29.32
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0827
	500mL	1	HNO3	Metals	

Comments

Signature

MK

Date

5/7/25

Well/Piezo ID:

MIN 2017-8D

Ground Water Sample Collection Record

Client: BEPC Date: 5/7/25
 Project No: Time: 0835
 Site Location: AVS LOS PLANT Finish: 0920
 Weather Conds: Sunny, cool Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 44.34 c. Casing Material PVC

Pump Settings 20/4 @ 50psi

b. Water Table Depth 38.54 d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model

Serial Number

YSI

5320084101

HACH

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0901	INITIAL 5L	9.1	.38	2130	7.97	-303.4	5.01	Brown	38.60
0905	6 L	9.2	.30	2731	7.98	-304.0	5.07		38.60
0909	7 L	9.2	.29	2730	7.98	-304.4	4.86		38.61
0912	8 L	9.2	.28	2730	7.96	-309	5.17		38.60
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0914
	500mL	1	HNO3	Metals	

Comments

Signature

man

Date

5/7/25



Minnesota Valley Testing Laboratories, Inc.
2616 East Broadway Avenue
Bismarck, ND 58501

Phone: (701) 258-9720

Toll Free: (800) 279-6885

Fax: (701) 258-9724

Lab Use Only

Chain of Custody

Page 1 of 2

Work Order #

Lab Use Only

Company Name and Address

Basin Electric Power Coop.
Leland Olds Station
3901 Highway 200A
Stanton, ND 58571

Account #

2040

Phone #

701-745-7238 701-557-5488

Contact

Mark Dihle

Emails

mdihle@bepec.com aknutson@bepec.com

Name of Sampler

Mariah Knutson

Billing Address (indicate if different from above)

Attn: Liabilities

Quote Number

Date Submitted

5/7/2025

Project Name/Number

LOS CCR Wells

Purchase Order #

790708-04

Lab Use Only		Sample Matrix	Date	Time	Bottles	YN	Analysis Required				
Lab	Sample ID	GW - Groundwater	Sampled	Sampled							
	MW-2017-1	GW	5/6/2025	817	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-2	GW	5/6/2025	911	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-3	GW	5/6/2025	953	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-4	GW	5/6/2025	1048	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-10	GW	5/6/2025	1131	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-11	GW	5/6/2025	1259	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-7	GW	5/6/2025	1345	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	DUP	GW	5/6/2025	1345	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
	MW-2017-8	GW	5/7/2025	827	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH				
Transferred by		Date	Time	Received by		Date	Time	Temp	ROI	Therm. #	
1. MILLENIUM EXPRESS		5/7/2025	NOON						Y / N		
2									Y / N		

Please submit the top copy with your samples. We will return the completed original with your results.



Minnesota Valley Testing Laboratories, Inc.
2616 East Broadway Avenue
Bismarck, ND 58501

Phone: (701) 258-9720

Toll Free: (800) 279-6885

Fax: (701) 258-9724

Lab Use Only

Chain of Custody

Page 2 of 2

Work Order #

Lab Use Only

Company Name and Address

Basin Electric Power Coop.
Leland Olds Station
3901 Highway 200A
Stanton, ND 58571

Billing Address (indicate if different from above)
Attn: Liabilities

Account #

2040

Phone #

701-745-7238 701-557-5488

Contact

Mark Dihle

Emails

mdihle@bepc.com aknutson@bepc.com

Name of Sampler

Mariah Knutson

Quote Number

Date Submitted

9/18/2024

Project Name/Number

ND0025232

Purchase Order #

790708-04

Lab Use Only	Sample ID	Sample Matrix GW - Groundwater	Date Sampled	Time Sampled	Bottles	Y/N	Analysis Required
Lab							
	MW-2017-8D	GW	5/7/2025	914	2	N	B, Ca, Cl, F, SO ₄ , TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH

Comments:

Transferred by	Date	Time	Received by	Date	Time	Temp	ROI	Therm. #
1. MILLENNIUM EXPRESS	5/7/2025	NOON					Y / N	
2.							Y / N	

1657.89

* Depth to water as measured from the top of PVC casing.

* Depth to water as measured from the top of PVC casing.

Well/Piezo ID:

MW-2017 1

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: Time: 0744
 Site Location: AVS LOS PIANT Finish: 0819
 Weather Conds: Foggy 100° Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length 25.10 c. Casing Material PVC

Pump Settings 28/2 @ 40 psi

b. Water Table Depth ↓ d. Casing Diameter

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0800	INITIAL 4L	11.2	.37	1898	6.97	-342.2	2.37	clear	25.15
0804	5 L	11.1	.59	1898	6.97	-344.8	2.22	↓	25.15
0808	6 L	11.2	.58	1899	6.98	-344.1	2.15	↓	25.15
0812	7 L	11.1	.62	1899	6.97	-342.0	2.00	↓	25.10
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0813
	500mL	1	HNO3	Metals	↓

Comments

Signature

[Signature]

Date

8-4-25

Well/Piezo ID:

MN-2017-2

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: Time: 0820
 Site Location: AVS LOS PLANT Finish: 0900
 Weather Conds: Foggy 60° Collector(s) MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____ c. Casing Material PVC

Pump Settings 27/3 @ 60psi

b. Water Table Depth 22.00 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model

YSI

Serial Number

5320084101

HACH

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0846	INITIAL 4.5L	11.3	.33	1411	7.16	-343.1	4.99	clear	22.07
0850	5.5L	11.2	.31	1408	7.16	-342.5	4.45		22.08
0854	10.5L	11.2	.29	1397	7.16	-340.3	4.70		22.02
0858	7.5L	11.1	.29	1395	7.16	-340.0	4.37		22.04
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0900
	500mL	1	HNO3	Metals	

Comments

Signature

Date

8-4-25

Well/Piezo ID:

MW-2017-3

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: Time: 0910
 Site Location: AVS LAS PLANT Finish: 0932
 Weather Conds: Foggy 60' Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____ c. Casing Material PVC

Pump Settings: 27/3 e. 60psi

b. Water Table Depth 23.96 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model

YSI

Serial Number

5320084101

HACH

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1

<0.5

<5

Time	Volume Removed (gal)	T° (C) +/- 0.2	DO mg/L +/- 10%	Spec. Cond (µs/cm) +/- 3%	pH +/- 0.1	ORP +/- 10%	Turbidity (NTU) +/- 10%	Color	DTW 0.33 ft
0919	INITIAL 10L	10.8	0.25	1524	7.24	-338.5	3.24	clear	24.30
0923	7 L	10.9	0.22	1517	7.25	-339.5	3.06	↓	24.29
0927	8 L	10.8	0.21	1517	7.24	-339.8	2.98	↓	24.30
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0928
	500mL	1	HNO3	Metals	↓

Comments

Signature

Man

Date

8-4-25

Well/Piezo ID:

MW. 2017 4

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: _____ Time: 0947
 Site Location: AVS LAS Plant Finish: 1029
 Weather Conds: cloudy w/ Collector(s): ML

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒a. Total Well Length _____ c. Casing Material PVCPump Settings: 27/3 e kopsib. Water Table Depth 25.81 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pumpb. Field Testing Equipment Used: Make _____ Model _____
 YSI
 HACH

Serial Number

5320084101

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
<u>1006</u>	<u>INITIAL 4L</u>	<u>11.5</u>	<u>0.33</u>	<u>1348</u>	<u>7.12</u>	<u>348.1</u>	<u>19.3</u>	<u>clear</u>	<u>25.86</u>
<u>1010</u>	<u>5 L</u>	<u>11.5</u>	<u>0.30</u>	<u>1356</u>	<u>7.13</u>	<u>348.8</u>	<u>22.4</u>		<u>25.91</u>
<u>1014</u>	<u>6 L</u>	<u>11.5</u>	<u>0.24</u>	<u>1361</u>	<u>7.15</u>	<u>349.4</u>	<u>12.6</u>		<u>25.90</u>
<u>1018</u>	<u>7 L</u>	<u>11.4</u>	<u>0.22</u>	<u>1364</u>	<u>7.13</u>	<u>349.9</u>	<u>11.9</u>		<u>25.91</u>
<u>1022</u>	<u>8 L</u>	<u>11.6</u>	<u>0.21</u>	<u>1368</u>	<u>7.14</u>	<u>350.2</u>	<u>11.4</u>		<u>25.89</u>
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	<u>1L</u>	<u>1</u>		<u>TDS/Anions</u>	<u>1023</u>
	<u>500mL</u>	<u>1</u>	<u>HNO3</u>	<u>Metals</u>	

Comments _____

Signature manDate 8-4-25

Well/Piezo ID:

MW-2017-10

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-75
 Project No: _____ Time: 1033
 Site Location: AVS - LOS PLANT Finish: 1107
 Weather Conds: cloudy Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____ c. Casing Material PVC Pump Settings: 20/4 @ 50psi
 b. Water Table Depth 33.70 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make _____ Model _____
 YSI _____
 HACH _____

Serial Number

5320084101

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C) +/- 0.2	DO mg/L +/- 10%	Spec. Cond (µs/cm) +/- 3%	pH +/- 0.1	ORP +/- 10%	Turbidity ✓ (NTU) +/- 10%	Color	DTW 0.33 ft
Stabilization									
1050	INITIAL 4L	12.4	0.16	1013	7.50	-354.2	1.55	clear	33.80
1054	5 L	12.4	0.14	1011	7.49	-354.5	1.46	↓	33.81
1058	10 L	12.4	0.13	1011	7.49	-354.9	0.83	↓	33.80
1102	7 L	12.5	0.12	1010	7.49	-354.9	0.82	↓	33.79
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail
 Has required volume been removed Yes ☐ No ☐ N/A ☐
 Has required turbidity been reached Yes ☐ No ☐ N/A ☐
 Have parameters stabilized Yes ☐ No ☐ N/A ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1103
	500mL	1	HNO3	Metals	↓

Comments _____

Signature manDate 8-4-75

Well/Piezo ID:

MW-2017 11

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: Time: 1146
 Site Location: AVS Las Plant Finish: 1230
 Weather Conds: cloudy, nice Collector(s): MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____ c. Casing Material PVC Pump Settings 220/4 @ 50psi
 b. Water Table Depth 39.40 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
1209	INITIAL FL	13.2	0.19	923	7.44	-319.5	0.51	clear	39.40
1213	5 L	13.1	0.17	922	7.45	-320.5	0.58		39.40
1217	10 L	13.2	0.15	924	7.45	-335.6	0.62		39.39
1221	7 L	13.1	0.13	925	7.45	-351.9	0.63		39.40
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☐ ☐ ☐
 Has required turbidity been reached ☐ ☐ ☐
 Have parameters stabilized ☐ ☐ ☐
 If no or N/A - Explain below.

DUP

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1221
	500mL	1	HNO3	Metals	

Comments

Signature Man

Date 8-4-25

Well/Piezo ID:

MW. 2017.7

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: Time: 1234
 Site Location: AVS LOS Plant Finish: 1313
 Weather Conds: cloudy nice Collector(s) MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____ c. Casing Material PVC

Pump Settings 210/4 e loops

b. Water Table Depth 39.39 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model
YSI
HACH

Serial Number

5320084101

20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
<0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
1257	INITIAL 3.5	12.1	0.24	1070	7.51	-363.9	2.30	yellow	39.39
1301	4.5 L	11.9	0.23	1072	7.51	-364.7	2.32	brown	39.39
1305	5.5 L	11.9	0.20	1071	7.51	-364.1	.87	↓	39.39
1309	6.5 L	11.8	0.18	1073	7.51	-364.5	.90	↓	39.39
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail
 Has required volume been removed Yes ☐ No ☐ N/A ☐
 Has required turbidity been reached Yes ☐ No ☐ N/A ☐
 Have parameters stabilized Yes ☐ No ☐ N/A ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	1310
	500mL	1	HNO3	Metals	↓

Comments _____

Signature



Date

8-4-25

Well/Piezo ID:

MW-20178

Ground Water Sample Collection Record

Client: BEPC Date: 8-4-25
 Project No: _____ Time: 1310
 Site Location: AVS LOS PLANT Finish: 1353
 Weather Conds: WARM Collector(s): ME. ML

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____

c. Casing Material PVCPump Settings 26/4 @ 40psib. Water Table Depth 28.18

d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
YSI 5320084101
HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
<0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
<u>1336</u>	<u>INITIAL 3.5L</u>	<u>10.8</u>	<u>.28</u>	<u>4825</u>	<u>7.41</u>	<u>351.6</u>	<u>14.2</u>	<u>clear</u>	<u>28.20</u>
<u>1340</u>	<u>4.5 L</u>	<u>10.9</u>	<u>.25</u>	<u>4845</u>	<u>7.41</u>	<u>352.3</u>	<u>13.6</u>		<u>28.19</u>
<u>1344</u>	<u>5.5 L</u>	<u>10.9</u>	<u>.26</u>	<u>4891</u>	<u>7.40</u>	<u>364.4</u>	<u>12.5</u>		<u>28.19</u>
<u>1348</u>	<u>10.5 L</u>	<u>10.9</u>	<u>.31</u>	<u>4721</u>	<u>7.41</u>	<u>365.0</u>	<u>12.3</u>		<u>28.19</u>
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	<u>1L</u>	<u>1</u>		<u>TDS/Anions</u>	<u>1349</u>
	<u>500mL</u>	<u>1</u>	<u>HNO3</u>	<u>Metals</u>	<u>↓</u>

Comments _____

Signature ME. MLDate 8-4-25

Well/Piezo ID:

MW-2017-8D

Ground Water Sample Collection Record

Client: BEPC Date: 8-5-25
 Project No: Time: _____
 Site Location: AVS LOS Plant Finish: _____
 Weather Conds: Rainy Cool Collector(s) MK

WATER LEVEL DATA: (measured from Top of Casing)

Well ☒

a. Total Well Length _____ c. Casing Material PVC Pump Settings 24/4 @ 50PSI
 b. Water Table Depth 38.02 d. Casing Diameter _____

WELL PURGING DATA

a. Purge Method Dedicated Bladder Pump

b. Field Testing Equipment Used: Make Model Serial Number
 YSI 5320084101
 HACH 20030C084551

c. Field Testing Equipment Calibration Documentation Found in Field Notebook # 1 Page # 1
 <0.5 <5

Time	Volume Removed (gal)	T° (C)	DO mg/L	Spec. Cond (µs/cm)	pH	ORP	Turbidity (NTU)	Color	DTW
Stabilization		+/- 0.2	+/- 10%	+/- 3%	+/- 0.1	+/- 10%	+/- 10%		0.33 ft
0752	INITIAL 5L	10.9	.43	2897	7.94	-343.8	5.03	Brown	38.04
0756	6 L	10.7	.39	2904	7.95	-342.0	4.84	↓	38.03
0800	7 L	10.6	.35	2891	7.95	-342.1	4.78	↓	38.05
0804	8 L	10.7	.32	2887	7.94	-341.4	4.67	↓	38.04
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								
	L								

e. Acceptance criteria pass/fail Yes No N/A
 Has required volume been removed ☒ ☐ ☐
 Has required turbidity been reached ☒ ☐ ☐
 Have parameters stabilized ☒ ☐ ☐
 If no or N/A - Explain below.

SAMPLE COLLECTION:

Method: Bladder Pump

Sample ID	Container Type	No. of Containers	Preservation	Analysis	Time
	1L	1		TDS/Anions	0805
	500mL	1	HNO3	Metals	↓

Comments

Signature

Man

Date

8-5-25



MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com



Account #: 2040

Client: Basin Electric Power Cooperative



Minnesota Valley Testing Laboratories, Inc.
2616 East Broadway Avenue
Bismarck, ND 58501
Phone: (701) 258-9720
Toll Free: (800) 279-6885 Fax: (701) 258-9724

Basin Electric Power Cooperative

WO: 94620



Chain of Custody

Page 1 of 2

Order #
Only

Company Name and Address Basin Electric Power Cooperative Leland Olds Station 3801 Highway 200A Stanton, ND 58571 Billing Address (Indicate if different from above) Attn: Liability		Account # 2040	Phone # 701-745-7238 701-557-5485
		Contact Mark Dohle	Emails mdohle@beco.com aknutson@beco.com
		Name of Sampler Mariah Knutson	
		Quote Number	Date Submitted 8/5/2025
		Project Name/Number LOS CCR Wells	Purchase Order # 790708-04

Lab Use Only	Sample ID	Sample Matrix GW - Groundwater	Date Sampled	Time Sampled	Temp	Filtered	Analysis Required
001	MW-2017-1	GW	8/4/2025	813	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
002	MW-2017-2	GW	8/4/2025	900	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
003	MW-2017-3	GW	8/4/2025	928	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
004	MW-2017-4	GW	8/4/2025	1023	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
005	MW-2017-10	GW	8/4/2025	1103	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
006	MW-2017-11	GW	8/4/2025	1221	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
007	DUP	GW	8/4/2025	1221	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
008	MW-2017-7	GW	8/4/2025	1310	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
009	MW-2017-8	GW	8/4/2025	1349	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH

Transferred by	Date	Time	Received by	Date	Time	Temp	ROI	Therm. #
1. MILLENNIUM EXPRESS	8/5/2025	NOON	[Signature]	8/5/25	1519	3.2°C	Y/N	74419
2.							Y/N	

Please submit the top copy with your samples. We will return the completed original with your results.


MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative

 Minnesota Valley Testing Laboratories, Inc. 2616 East Broadway Avenue Bismarck, ND 58501 Phone: (701) 258-9720 Toll Free: (800) 279-8885 Fax: (701) 258-9724		Chain of Custody Page <u>2</u> of <u>2</u>						
Company Name and Address Basin Electric Power Coop. Leland Olds Station 3901 Highway 200A Stanton, ND 58571 Billing Address (indicate if different from above) <u>Attn: Liabilities</u>		Account # 2040 Contact Mark Dille Name of Sampler Marlah Knutson Quote Number Project Name/Number ND0025232	Phone # 701-745-7238 701-557-5488 Emails mdille@bepc.com aknutson@bepc.com Date Submitted 8/18/2024 Purchase Order # 790708-04					
Lab Use Only Lab	Sample ID	Sample Matrix GW - Groundwater	Date Sampled	Time Sampled	# of	Filtered	Analysis Required B, Ca, Cl, F, SO ₄ , TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH	
010	MW-2017-8D	GW	8/5/2025	805	2	N		
Comments:								
Transferred by	Date	Time	Received by	Date	Time	Temp	ROI	Therm. #
1. MILLENNIUM EXPRESS	8/5/2025	NOON	<i>[Signature]</i>	8/18/25	1515	3.2°C	Y/N	749.58
2.							Y/N	

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 17 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com



Account #: 2040 **Client:** Basin Electric Power Cooperative
Workorder: LOS CCR Wells (85896) **PO:** 790708-04

Mark Dihle
Basin Electric Power Cooperative
1717 E. Interstate Avenue
Bismarck, ND 58503

Certificate of Analysis**Approval**

All data reported has been reviewed and approved by:

C. Carroll

Claudette Carroll, Lab Manager Bismarck, ND

Analyses performed under Minnesota Department of Health Accreditation conforms to the current TNI standards.

NEW ULM LAB CERTIFICATIONS:
MN LAB # 027-015-125 ND WW/DW # R-040

BISMARCK LAB CERTIFICATIONS:
MN LAB # 038-999-267 ND W/DW # ND-016

Workorder Comments

All analytes with dilution factors greater than 1 (displayed in DF column) required dilution due to matrix or high concentration of target analyte unless otherwise noted and reporting limits (RDL column) have been adjusted accordingly.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 1 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896001	Date Collected:	05/06/2025 08:17		Matrix:	Groundwater	
Sample ID:	MW-2017-1	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	355	mg/L	25	5		05/14/2025 10:01	
Method: EPA 6010D							
Boron	0.54	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:18	
Calcium	217	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:51	
Magnesium	91.2	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:51	
Potassium	6.09	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:51	
Sodium	112	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:51	
Method: SM2320 B-2021							
Alkalinity, Total	588	mg/L as CaCO3	20.5	1		05/08/2025 18:17	
Bicarbonate	588	mg/L as CaCO3	20.5	1		05/08/2025 18:17	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 18:17	
Method: SM4500 H+ B-2021							
pH	7.3	units	0.1	1		05/08/2025 18:17	*
Method: SM4500-Cl-E 2021							
Chloride	14.7	mg/L	2.0	1		05/13/2025 10:06	
Method: SM4500-F-C-2021							
Fluoride	0.36	mg/L	0.1	1		05/08/2025 18:17	
Method: USGS I-1750-85							
Total Dissolved Solids	1250	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 2 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896002	Date Collected:	05/06/2025 09:11		Matrix:	Groundwater	
Sample ID:	MW-2017-2	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	271	mg/L	5	1		05/14/2025 10:14	
Method: EPA 6010D							
Boron	1.50	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:18	
Calcium	78.8	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:53	
Magnesium	27.8	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:53	
Potassium	5.16	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:53	
Sodium	142	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:53	
Method: SM2320 B-2021							
Alkalinity, Total	218	mg/L as CaCO3	20.5	1		05/08/2025 18:28	
Bicarbonate	218	mg/L as CaCO3	20.5	1		05/08/2025 18:28	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 18:28	
Method: SM4500 H+ B-2021							
pH	7.6	units	0.1	1		05/08/2025 18:28	*
Method: SM4500-Cl-E 2021							
Chloride	11.3	mg/L	2.0	1		05/13/2025 10:07	
Method: SM4500-F-C-2021							
Fluoride	0.48	mg/L	0.1	1		05/08/2025 18:28	
Method: USGS I-1750-85							
Total Dissolved Solids	711	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 3 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896003	Date Collected:	05/06/2025 09:53		Matrix:	Groundwater	
Sample ID:	MW-2017-3	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	156	mg/L	5	1		05/14/2025 10:15	
Method: EPA 6010D							
Boron	1.51	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:19	
Calcium	111	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:54	
Magnesium	39.7	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:54	
Potassium	6.87	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:54	
Sodium	195	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:54	
Method: SM2320 B-2021							
Alkalinity, Total	533	mg/L as CaCO3	20.5	1		05/08/2025 18:39	
Bicarbonate	533	mg/L as CaCO3	20.5	1		05/08/2025 18:39	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 18:39	
Method: SM4500 H+ B-2021							
pH	7.6	units	0.1	1		05/08/2025 18:39	*
Method: SM4500-Cl-E 2021							
Chloride	11.0	mg/L	2.0	1		05/13/2025 10:17	
Method: SM4500-F-C-2021							
Fluoride	0.50	mg/L	0.1	1		05/08/2025 18:39	
Method: USGS I-1750-85							
Total Dissolved Solids	882	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 4 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896004	Date Collected:	05/06/2025 10:48		Matrix:	Groundwater	
Sample ID:	MW-2017-4	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	298	mg/L	25	5		05/14/2025 10:16	
Method: EPA 6010D							
Boron	1.20	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:20	
Calcium	151	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:55	
Magnesium	34.1	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:55	
Potassium	9.30	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:55	
Sodium	123	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:55	
Method: SM2320 B-2021							
Alkalinity, Total	329	mg/L as CaCO3	20.5	1		05/08/2025 18:50	
Bicarbonate	329	mg/L as CaCO3	20.5	1		05/08/2025 18:50	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 18:50	
Method: SM4500 H+ B-2021							
pH	7.5	units	0.1	1		05/08/2025 18:50	*
Method: SM4500-Cl-E 2021							
Chloride	10.8	mg/L	2.0	1		05/13/2025 10:18	
Method: SM4500-F-C-2021							
Fluoride	0.78	mg/L	0.1	1		05/08/2025 18:50	
Method: USGS I-1750-85							
Total Dissolved Solids	886	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 5 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896005	Date Collected:	05/06/2025 11:31		Matrix:	Groundwater	
Sample ID:	MW-2017-10	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	284	mg/L	25	5		05/14/2025 10:17	
Method: EPA 6010D							
Boron	0.88	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:20	
Calcium	96.0	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:56	
Magnesium	27.5	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:56	
Potassium	4.99	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:56	
Sodium	108	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:56	
Method: SM2320 B-2021							
Alkalinity, Total	173	mg/L as CaCO3	20.5	1		05/08/2025 19:01	
Bicarbonate	173	mg/L as CaCO3	20.5	1		05/08/2025 19:01	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 19:01	
Method: SM4500 H+ B-2021							
pH	7.8	units	0.1	1		05/08/2025 19:01	*
Method: SM4500-Cl-E 2021							
Chloride	10.8	mg/L	2.0	1		05/13/2025 10:19	
Method: SM4500-F-C-2021							
Fluoride	0.86	mg/L	0.1	1		05/08/2025 19:01	
Method: USGS I-1750-85							
Total Dissolved Solids	726	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 6 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896006	Date Collected:	05/06/2025 12:59		Matrix:	Groundwater	
Sample ID:	MW-2017-11	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	169	mg/L	5	1		05/14/2025 10:18	
Method: EPA 6010D							
Boron	1.30	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:21	
Calcium	66.6	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:57	
Magnesium	24.1	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:57	
Potassium	4.97	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:57	
Sodium	121	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:57	
Method: SM2320 B-2021							
Alkalinity, Total	255	mg/L as CaCO3	20.5	1		05/08/2025 19:12	
Bicarbonate	255	mg/L as CaCO3	20.5	1		05/08/2025 19:12	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 19:12	
Method: SM4500 H+ B-2021							
pH	7.8	units	0.1	1		05/08/2025 19:12	*
Method: SM4500-Cl-E 2021							
Chloride	11.2	mg/L	2.0	1		05/13/2025 10:20	
Method: SM4500-F-C-2021							
Fluoride	0.76	mg/L	0.1	1		05/08/2025 19:12	
Method: USGS I-1750-85							
Total Dissolved Solids	606	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 7 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896007	Date Collected:	05/06/2025 13:45		Matrix:	Groundwater	
Sample ID:	MW-2017-7	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	224	mg/L	5	1		05/14/2025 10:20	
Method: EPA 6010D							
Boron	2.23	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:22	
Calcium	72.2	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:59	
Magnesium	21.9	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:59	
Potassium	4.03	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:59	
Sodium	155	mg/L	1	1	05/07/2025 17:00	05/12/2025 15:59	
Method: SM2320 B-2021							
Alkalinity, Total	221	mg/L as CaCO3	20.5	1		05/08/2025 19:23	
Bicarbonate	221	mg/L as CaCO3	20.5	1		05/08/2025 19:23	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 19:23	
Method: SM4500 H+ B-2021							
pH	7.8	units	0.1	1		05/08/2025 19:23	*
Method: SM4500-Cl-E 2021							
Chloride	11.4	mg/L	2.0	1		05/13/2025 10:21	
Method: SM4500-F-C-2021							
Fluoride	1.21	mg/L	0.1	1		05/08/2025 19:23	
Method: USGS I-1750-85							
Total Dissolved Solids	721	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 8 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID: 85896008	Date Collected: 05/06/2025 13:45	Matrix: Groundwater
Sample ID: DUP	Date Received: 05/07/2025 14:44	Collector: Client

Temp @ Receipt (C): 4.6**Received on Ice:** Yes

Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
-----------	---------	-------	-----	----	----------	----------	------

Method: ASTM D516-16

Sulfate	261	mg/L	25	5		05/14/2025 10:21	
---------	-----	------	----	---	--	------------------	--

Method: EPA 6010D

Boron	2.32	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:24	
Calcium	74.5	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:00	
Magnesium	22.7	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:00	
Potassium	4.14	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:00	
Sodium	161	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:00	

Method: SM2320 B-2021

Alkalinity, Total	214	mg/L as CaCO3	20.5	1		05/08/2025 19:33	
Bicarbonate	214	mg/L as CaCO3	20.5	1		05/08/2025 19:33	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 19:33	

Method: SM4500 H+ B-2021

pH	7.8	units	0.1	1		05/08/2025 19:33	*
----	-----	-------	-----	---	--	------------------	---

Method: SM4500-Cl-E 2021

Chloride	11.4	mg/L	2.0	1		05/13/2025 10:23	
----------	------	------	-----	---	--	------------------	--

Method: SM4500-F-C-2021

Fluoride	1.22	mg/L	0.1	1		05/08/2025 19:33	
----------	------	------	-----	---	--	------------------	--

Method: USGS I-1750-85

Total Dissolved Solids	741	mg/L	10	1		05/09/2025 14:55	
------------------------	-----	------	----	---	--	------------------	--

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 9 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896009	Date Collected:	05/07/2025 08:27		Matrix:	Groundwater	
Sample ID:	MW-2017-8	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	1630	mg/L	50	10		05/14/2025 10:22	
Method: EPA 6010D							
Boron	0.44	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:25	
Calcium	128	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:01	
Magnesium	115	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:01	
Potassium	9.48	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:01	
Sodium	1080	mg/L	5	5	05/07/2025 17:00	05/12/2025 16:29	
Method: SM2320 B-2021							
Alkalinity, Total	915	mg/L as CaCO3	20.5	1		05/08/2025 19:44	
Bicarbonate	915	mg/L as CaCO3	20.5	1		05/08/2025 19:44	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 19:44	
Method: SM4500 H+ B-2021							
pH	7.8	units	0.1	1		05/08/2025 19:44	*
Method: SM4500-Cl-E 2021							
Chloride	26.5	mg/L	2.0	1		05/13/2025 10:24	
Method: SM4500-F-C-2021							
Fluoride	0.39	mg/L	0.1	1		05/08/2025 19:44	
Method: USGS I-1750-85							
Total Dissolved Solids	3680	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 10 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	85896010	Date Collected:	05/07/2025 09:14		Matrix:	Groundwater	
Sample ID:	MW-2017-8D	Date Received:	05/07/2025 14:44		Collector:	Client	
Temp @ Receipt (C):	4.6	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	345	mg/L	25	5		05/14/2025 10:23	*
Method: EPA 6010D							
Boron	0.69	mg/L	0.1	1	05/07/2025 17:00	05/14/2025 09:26	
Calcium	8.50	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:03	
Magnesium	3.75	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:03	
Potassium	4.00	mg/L	1	1	05/07/2025 17:00	05/12/2025 16:03	
Sodium	806	mg/L	5	5	05/07/2025 17:00	05/12/2025 16:31	
Method: SM2320 B-2021							
Alkalinity, Total	1137	mg/L as CaCO3	20.5	1		05/08/2025 21:47	
Bicarbonate	1136	mg/L as CaCO3	20.5	1		05/08/2025 21:47	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		05/08/2025 21:47	
Method: SM4500 H+ B-2021							
pH	8.3	units	0.1	1		05/08/2025 21:47	*
Method: SM4500-Cl-E 2021							
Chloride	16.6	mg/L	2.0	1		05/13/2025 10:25	
Method: SM4500-F-C-2021							
Fluoride	0.68	mg/L	0.1	1		05/08/2025 21:47	
Method: USGS I-1750-85							
Total Dissolved Solids	1960	mg/L	10	1		05/09/2025 14:55	

Analysis Results Comments**Sulfate**

Matrix spike and/or matrix spike duplicate recovery was low; the associated laboratory control sample recovery was acceptable.

pH

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 11 of 14



MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com



Account #: 2040

Client: Basin Electric Power Cooperative

Basin Electric Power Coop
WO: 85896



Minnesota Valley Testing Laboratories, Inc.
2616 East Broadway Avenue
Bismarck, ND 58501

Phone: (701) 258-9720

Toll Free: (800) 279-6885

Fax: (701) 258-9724



ustody
of 2

Company Name and Address Basin Electric Power Coop Leland Olds Station 3901 Highway 200A Stanton, ND 58571		Account # 2040	Phone # 701-745-7238 701-557-5483						
Billing Address (Indicate if different from above) Attn: Liabilities		Contact Mark D'Hea	Emails mdhe@becp.com aknutson@becp.com						
		Name of Sampler Marlah Knutson							
		Quote Number	Date Submitted 5/7/2025						
		Project Name/Number LOS CCR Wells	Purchase Order # 790708-04						
Lab Use Only	Sample ID	Sample Matrix GW - Groundwater	Date Sampled	Time Sampled	Vol	Filtered	Analysis Required		
001	NW-2017-1	GW	5/6/2025	817	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
002	NW-2017-2	GW	5/6/2025	911	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
003	NW-2017-3	GW	5/6/2025	953	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
004	NW-2017-4	GW	5/6/2025	1048	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
005	NW-2017-10	GW	5/6/2025	1131	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
006	NW-2017-11	GW	5/6/2025	1269	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
007	NW-2017-7	GW	5/6/2025	1345	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
008	DUP	GW	5/6/2025	1345	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
009	NW-2017-8	GW	5/7/2025	827	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH		
Transferred by		Date	Time	Received by	Date	Time	Temp	SOI	Therm #
1. MILLENNIUM EXPRESS		5/7/2025	NOON	Mark D'Hea	5/7/2025	1:45 PM	41.0°C	Y/N	WPS9
2.								Y/N	

Please submit the top copy with your samples. We will return the completed original with your results.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 12 of 14

MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTI.com



Account #: 2040

Client: Basin Electric Power Cooperative

[illegible]

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 13 of 14



MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com



Account #: 2040

Client: Basin Electric Power Cooperative



Sample Condition Checklist

Date: 7 May 25 Time: 1609 Analyst: PN

Work Order #: 895896

Containers Supplied by MVTL: ☒ Yes ☐ No (Designate customer supplied containers as "Other" in container size column)

Comments:

Container Size (mL)																							
Number of Bottles	Container Size (mL)						Container Type				Preservation	pH	Sample IDs Preservation reagent added Date/Time Analyst	Unique ID of preservation reagent added	Sample pH after preservation	Required for HNO ₃ samples only (24 hours later) Sample ID pH Recheck Result Date/Time/Analyst							
	F-(500) = Filtered						CG = Clear Glass, P = Plastic, AG = Amber Glass																
10	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
10	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	(125)	(250)	(500)	F-(500)	(1000)	Other	(CG)	(P)	(AG)	Other	NONE	HNO ₃	H ₂ SO ₄	NaOH	NaOH/ZnAcet	HCl	<2	>12					
	Oil and grease						(CG)	(P)	(AG)	Other	HCl			n/a									
	TOC Vials						(G)	(AG)			H ₃ PO ₄			n/a									
	DOC Vials						(G)	(AG)			None			H ₃ PO ₄			n/a						

*All samples requiring analyses performed outside of the Bismarck laboratory (New Ulm and Sub-Contract) are not documented on this form.
*All samples requiring microbiological tests are not documented on this form.

Form #80-910025-2

M:\Documents\FORMS\Approved Templates\Bismarck\Waters\80-910025-2 Sample Condition Checklist
Page 1 of 1

Effective Date : 1 July 2024

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, May 20, 2025 7:56:39 AM

Page 14 of 14

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com



Account #: 2040 **Client:** Basin Electric Power Cooperative
Workorder: LOS CCR Wells (94620) **PO:** 790708-04

Mark Dihle
Basin Electric Power Cooperative
1717 E. Interstate Avenue
Bismarck, ND 58503

Certificate of Analysis**Approval**

All data reported has been reviewed and approved by:

C. Carroll

Claudette Carroll, Lab Manager Bismarck, ND

Analyses performed under Minnesota Department of Health Accreditation conforms to the current TNI standards.

NEW ULM LAB CERTIFICATIONS:
MN LAB # 027-015-125 ND WW/DW # R-040

BISMARCK LAB CERTIFICATIONS:
MN LAB # 038-999-267 ND W/DW # ND-016

Workorder Comments

All analytes with dilution factors greater than 1 (displayed in DF column) required dilution due to matrix or high concentration of target analyte unless otherwise noted and reporting limits (RDL column) have been adjusted accordingly.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620001	Date Collected:	08/04/2025 08:13		Matrix:	Groundwater	
Sample ID:	MW-2017-1	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	326	mg/L	25	5		08/08/2025 09:45	
Method: EPA 6010D							
Boron	0.44	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 08:54	
Calcium	231	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:36	
Magnesium	94.8	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:36	
Potassium	6.02	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:36	
Sodium	108	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:36	
Method: SM2320 B-2021							
Alkalinity, Total	630	mg/L as CaCO3	20.5	1		08/05/2025 18:48	
Bicarbonate	630	mg/L as CaCO3	20.5	1		08/05/2025 18:48	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 18:48	
Method: SM4500 H+ B-2021							
pH	7.2	units	0.1	1		08/05/2025 18:48	*
Method: SM4500-Cl-E 2021							
Chloride	16.4	mg/L	2.0	1		08/08/2025 12:13	
Method: SM4500-F-C-2021							
Fluoride	0.35	mg/L	0.1	1		08/05/2025 18:48	
Method: USGS I-1750-85							
Total Dissolved Solids	1230	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 2 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID: 94620002
Sample ID: MW-2017-2

Date Collected: 08/04/2025 09:00
Date Received: 08/05/2025 15:19

Matrix: Groundwater
Collector: Client

Temp @ Receipt (C): 3.2

Received on Ice: Yes

Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
-----------	---------	-------	-----	----	----------	----------	------

Method: ASTM D516-16

Sulfate	291	mg/L	5	1		08/08/2025 09:46	
---------	-----	------	---	---	--	------------------	--

Method: EPA 6010D

Boron	1.11	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 08:54	
Calcium	119	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:41	
Magnesium	43.8	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:41	
Potassium	5.85	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:41	
Sodium	154	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:41	

Method: SM2320 B-2021

Alkalinity, Total	403	mg/L as CaCO ₃	20.5	1		08/05/2025 18:58	
Bicarbonate	403	mg/L as CaCO ₃	20.5	1		08/05/2025 18:58	
Carbonate	<20.5	mg/L as CaCO ₃	20.5	1		08/05/2025 18:58	

Method: SM4500 H+ B-2021

pH	7.4	units	0.1	1		08/05/2025 18:58	*
----	-----	-------	-----	---	--	------------------	---

Method: SM4500-Cl-E 2021

Chloride	11.7	mg/L	2.0	1		08/08/2025 12:15	
----------	------	------	-----	---	--	------------------	--

Method: SM4500-F-C-2021

Fluoride	0.41	mg/L	0.1	1		08/05/2025 18:58	
----------	------	------	-----	---	--	------------------	--

Method: USGS I-1750-85

Total Dissolved Solids	916	mg/L	10	1		08/06/2025 13:48	
------------------------	-----	------	----	---	--	------------------	--

Analysis Results Comments

pH

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 3 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620003	Date Collected:	08/04/2025 09:28		Matrix:	Groundwater	
Sample ID:	MW-2017-3	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	136	mg/L	5	1		08/08/2025 09:47	*
Method: EPA 6010D							
Boron	1.25	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 08:57	
Calcium	112	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:42	
Magnesium	41.2	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:42	
Potassium	6.67	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:42	
Sodium	198	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:42	
Method: SM2320 B-2021							
Alkalinity, Total	651	mg/L as CaCO3	20.5	1		08/05/2025 20:21	
Bicarbonate	651	mg/L as CaCO3	20.5	1		08/05/2025 20:21	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 20:21	
Method: SM4500 H+ B-2021							
pH	7.5	units	0.1	1		08/05/2025 20:21	*
Method: SM4500-Cl-E 2021							
Chloride	11.3	mg/L	2.0	1		08/08/2025 12:16	
Method: SM4500-F-C-2021							
Fluoride	0.52	mg/L	0.1	1		08/05/2025 20:21	
Method: USGS I-1750-85							
Total Dissolved Solids	966	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**Sulfate**

Matrix spike and/or matrix spike duplicate recovery was low; the associated laboratory control sample recovery was acceptable.

pH

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 4 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620004	Date Collected:	08/04/2025 10:23		Matrix:	Groundwater	
Sample ID:	MW-2017-4	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	323	mg/L	25	5		08/08/2025 11:14	
Method: EPA 6010D							
Boron	1.18	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 08:57	
Calcium	163	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:39	
Magnesium	35.7	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:39	
Potassium	9.31	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:39	
Sodium	124	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:39	
Method: SM2320 B-2021							
Alkalinity, Total	365	mg/L as CaCO3	20.5	1		08/05/2025 20:32	
Bicarbonate	365	mg/L as CaCO3	20.5	1		08/05/2025 20:32	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 20:32	
Method: SM4500 H+ B-2021							
pH	7.4	units	0.1	1		08/05/2025 20:32	*
Method: SM4500-Cl-E 2021							
Chloride	11.2	mg/L	2.0	1		08/08/2025 12:17	
Method: SM4500-F-C-2021							
Fluoride	0.80	mg/L	0.1	1		08/05/2025 20:32	
Method: USGS I-1750-85							
Total Dissolved Solids	908	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 5 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620005	Date Collected:	08/04/2025 11:03		Matrix:	Groundwater	
Sample ID:	MW-2017-10	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	308	mg/L	25	5		08/08/2025 11:15	
Method: EPA 6010D							
Boron	0.83	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 08:58	
Calcium	94.9	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:43	
Magnesium	26.3	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:43	
Potassium	4.49	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:43	
Sodium	99.5	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:43	
Method: SM2320 B-2021							
Alkalinity, Total	180	mg/L as CaCO3	20.5	1		08/05/2025 20:42	
Bicarbonate	180	mg/L as CaCO3	20.5	1		08/05/2025 20:42	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 20:42	
Method: SM4500 H+ B-2021							
pH	7.7	units	0.1	1		08/05/2025 20:42	*
Method: SM4500-Cl-E 2021							
Chloride	10.9	mg/L	2.0	1		08/08/2025 12:23	
Method: SM4500-F-C-2021							
Fluoride	0.91	mg/L	0.1	1		08/05/2025 20:42	
Method: USGS I-1750-85							
Total Dissolved Solids	671	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 6 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620006	Date Collected:	08/04/2025 12:21		Matrix:	Groundwater	
Sample ID:	MW-2017-11	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	178	mg/L	5	1		08/08/2025 11:03	
Method: EPA 6010D							
Boron	1.25	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 08:59	
Calcium	63.4	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:45	
Magnesium	23.9	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:45	
Potassium	4.88	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:45	
Sodium	116	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:45	
Method: SM2320 B-2021							
Alkalinity, Total	267	mg/L as CaCO3	20.5	1		08/05/2025 20:53	
Bicarbonate	267	mg/L as CaCO3	20.5	1		08/05/2025 20:53	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 20:53	
Method: SM4500 H+ B-2021							
pH	7.7	units	0.1	1		08/05/2025 20:53	*
Method: SM4500-Cl-E 2021							
Chloride	11.5	mg/L	2.0	1		08/08/2025 12:24	
Method: SM4500-F-C-2021							
Fluoride	0.78	mg/L	0.1	1		08/05/2025 20:53	
Method: USGS I-1750-85							
Total Dissolved Solids	592	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 7 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620007	Date Collected:	08/04/2025 12:21		Matrix:	Groundwater	
Sample ID:	DUP	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	180	mg/L	5	1		08/08/2025 11:04	
Method: EPA 6010D							
Boron	1.24	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 09:00	
Calcium	62.0	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:46	
Magnesium	23.5	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:46	
Potassium	4.71	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:46	
Sodium	114	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:46	
Method: SM2320 B-2021							
Alkalinity, Total	268	mg/L as CaCO3	20.5	1		08/05/2025 21:03	
Bicarbonate	268	mg/L as CaCO3	20.5	1		08/05/2025 21:03	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 21:03	
Method: SM4500 H+ B-2021							
pH	7.7	units	0.1	1		08/05/2025 21:03	*
Method: SM4500-Cl-E 2021							
Chloride	11.5	mg/L	2.0	1		08/08/2025 12:25	
Method: SM4500-F-C-2021							
Fluoride	0.78	mg/L	0.1	1		08/05/2025 21:03	
Method: USGS I-1750-85							
Total Dissolved Solids	585	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 8 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID: 94620008
Sample ID: MW-2017-7

Date Collected: 08/04/2025 13:10
Date Received: 08/05/2025 15:19

Matrix: Groundwater
Collector: Client

Temp @ Receipt (C): 3.2

Received on Ice: Yes

Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	243	mg/L	5	1		08/08/2025 11:06	
Method: EPA 6010D							
Boron	2.17	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 09:00	
Calcium	71.4	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:47	
Magnesium	21.9	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:47	
Potassium	3.90	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:47	
Sodium	147	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:47	
Method: SM2320 B-2021							
Alkalinity, Total	234	mg/L as CaCO3	20.5	1		08/05/2025 21:14	
Bicarbonate	234	mg/L as CaCO3	20.5	1		08/05/2025 21:14	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 21:14	
Method: SM4500 H+ B-2021							
pH	7.7	units	0.1	1		08/05/2025 21:14	*
Method: SM4500-Cl-E 2021							
Chloride	11.5	mg/L	2.0	1		08/08/2025 12:26	
Method: SM4500-F-C-2021							
Fluoride	1.15	mg/L	0.1	1		08/05/2025 21:14	
Method: USGS I-1750-85							
Total Dissolved Solids	721	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 9 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620009	Date Collected:	08/04/2025 13:49		Matrix:	Groundwater	
Sample ID:	MW-2017-8	Date Received:	08/05/2025 15:19		Collector:	Client	
Temp @ Receipt (C):	3.2	Received on Ice:	Yes				
Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
Method: ASTM D516-16							
Sulfate	1740	mg/L	50	10		08/08/2025 11:07	
Method: EPA 6010D							
Boron	0.43	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 09:01	
Calcium	127	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:48	
Magnesium	114	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:48	
Potassium	9.39	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:48	
Sodium	1020	mg/L	5	5	08/05/2025 16:43	08/11/2025 11:02	
Method: SM2320 B-2021							
Alkalinity, Total	932	mg/L as CaCO3	20.5	1		08/05/2025 21:24	
Bicarbonate	932	mg/L as CaCO3	20.5	1		08/05/2025 21:24	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 21:24	
Method: SM4500 H+ B-2021							
pH	7.7	units	0.1	1		08/05/2025 21:24	*
Method: SM4500-Cl-E 2021							
Chloride	26.2	mg/L	2.0	1		08/08/2025 12:28	
Method: SM4500-F-C-2021							
Fluoride	0.40	mg/L	0.1	1		08/05/2025 21:24	
Method: USGS I-1750-85							
Total Dissolved Solids	3620	mg/L	10	1		08/06/2025 13:48	

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 10 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative**Analytical Results**

Lab ID:	94620010	Date Collected:	08/05/2025 08:05	Matrix:	Groundwater
Sample ID:	MW-2017-8D	Date Received:	08/05/2025 15:19	Collector:	Client

Temp @ Receipt (C):	3.2	Received on Ice:	Yes
----------------------------	-----	-------------------------	-----

Parameter	Results	Units	RDL	DF	Prepared	Analyzed	Qual
-----------	---------	-------	-----	----	----------	----------	------

Method: ASTM D516-16

Sulfate	384	mg/L	25	5		08/08/2025 11:08	
---------	-----	------	----	---	--	------------------	--

Method: EPA 6010D

Boron	0.67	mg/L	0.1	1	08/05/2025 16:43	08/08/2025 09:02	
Calcium	8.30	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:49	
Magnesium	3.59	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:49	
Potassium	3.85	mg/L	1	1	08/05/2025 16:43	08/11/2025 10:49	
Sodium	715	mg/L	5	5	08/05/2025 16:43	08/11/2025 11:02	

Method: SM2320 B-2021

Alkalinity, Total	1152	mg/L as CaCO3	20.5	1		08/05/2025 21:36	
Bicarbonate	1152	mg/L as CaCO3	20.5	1		08/05/2025 21:36	
Carbonate	<20.5	mg/L as CaCO3	20.5	1		08/05/2025 21:36	

Method: SM4500 H+ B-2021

pH	8.1	units	0.1	1		08/05/2025 21:36	*
----	-----	-------	-----	---	--	------------------	---

Method: SM4500-Cl-E 2021

Chloride	16.2	mg/L	2.0	1		08/08/2025 12:29	
----------	------	------	-----	---	--	------------------	--

Method: SM4500-F-C-2021

Fluoride	0.65	mg/L	0.1	1		08/05/2025 21:36	
----------	------	------	-----	---	--	------------------	--

Method: USGS I-1750-85

Total Dissolved Solids	1930	mg/L	10	1		08/06/2025 13:48	
------------------------	------	------	----	---	--	------------------	--

Analysis Results Comments**pH**

Sample analyzed beyond holding time.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 11 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative

QC Results Summary						WO #:		94620	
Sulfate		Units: mg/L							
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB			100	100.0		85	115		
LFB			100	100.0		85	115		
LFB			100	96.2		85	115		
LFB			100	91.5		85	115		
LFB			100	106.0		85	115		
LFB			100	105.0		85	115		
LFB			100	100.0		85	115		
MB		<5							
MB		<5							
MB		<5							
MB		<5							
MB		<5							
MB		<5							
MS/MSD	94108017		100	73.0	74.5	85	115	0.4	20
MS/MSD	94445003		500	98.3	98.0	85	115	0.7	20
MS/MSD	94620003		100	82.5	81.7	85	115	0.5	20
MS/MSD	94639003		100	78.8	80.6	85	115	1.0	20
MS/MSD	94639013		500	89.9	88.2	85	115	1.0	20
MS/MSD	94652001		100	94.5	95.5	85	115	1.1	20
Chloride		Units: mg/L							
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB			30	96.3		90	110		
LFB			30	96.3		90	110		
LFB			30	96.2		90	110		
LFB			30	95.4		90	110		
LFB			30	95.5		90	110		
MB		<2.0							
MB		<2.0							

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM



MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVT.com



Account #: 2040

Client: Basin Electric Power Cooperative

Chloride									
Units: mg/L									
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
MB		<2.0							
MB		<2.0							
MB		<2.0							
MS/MSD	94639004		30	102.4	106.6	80	120	3.6	20
MS/MSD	94681001		30	96.4	95.7	80	120	0.0	20

Boron									
Units: mg/L									
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB-OE			0.4	99.6		85	115		
MB		<0.1							
MS/MSD	94525003		0.4	106.0	98.8	75	125	1.8	20
MS/MSD	94620002		0.4	91.2	95.8	75	125	1.2	20

Calcium									
Units: mg/L									
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB-MI			100	108.0		85	115		
MB		<1							
PDS/PDSO	94108014		500	99.7	101.0	75	125	0.8	20
DUP	94445004							0.4	20
PDS/PDSO	94525001		100	103.0	103.0	75	125	0.1	20
DUP	94620004							4.8	20
PDS/PDSO	94620005		100	95.6	96.3	75	125	0.4	20

Magnesium									
Units: mg/L									
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB-MI			100	108.0		85	115		
MB		<1							
PDS/PDSO	94108014		500	101.0	103.0	75	125	0.9	20
DUP	94445004							0.9	20
PDS/PDSO	94525001		100	102.0	102.0	75	125	0.4	20
DUP	94620004							3.0	20
PDS/PDSO	94620005		100	102.0	103.0	75	125	0.7	20

Potassium									
Units: mg/L									
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB-MI			100	106.0		85	115		

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative

Potassium		Units: mg/L							
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
MB		<1							
PDS/PDSO	94108014		500	103.0	101.0	75	125	1.3	20
DUP	94445004							2.0	20
PDS/PDSO	94525001		100	103.0	103.0	75	125	0.4	20
DUP	94620004							2.6	20
PDS/PDSO	94620005		100	102.0	102.0	75	125	0.0	20

Sodium		Units: mg/L							
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
LFB-MI			100	107.0		85	115		
MB		<1							
PDS/PDSO	94108014		500	99.6	101.0	75	125	0.6	20
DUP	94445004							1.5	20
PDS/PDSO	94525001		500	90.3	92.5	75	125	0.9	20
DUP	94620004							5.2	20
PDS/PDSO	94620005		100	94.2	93.6	75	125	0.3	20

Alkalinity, Total		Units: mg/L							
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
CRM			501	93.1		80	120		
LFB			410	96.6		90	110		
LFB			410	95.2		90	110		
LFB			410	93.1		90	110		
LFB			410	92.1		90	110		
MB		<20.5							
MB		<20.5							
MB		<20.5							
MB		<20.5							
MS/MSD	94445002		410	90.1	90.7	80	120	0.5	20
MS/MSD	94525002		410	91.3	101.9	80	120	3.1	20
MS/MSD	94620008		410	91.8	85.5	80	120	4.2	20

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 14 of 18

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

**Account #:** 2040**Client:** Basin Electric Power Cooperative

pH				Units: units					
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
CRM-PH			6	100.0					
CRM-PH			6	99.7					
CRM-PH			6	99.5					
CRM-PH			6	99.5					
DUP	9444006							0.1	20
DUP	94445004							1.1	20
DUP	94620003							0.8	20

Fluoride				Units: mg/L					
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
CRM-F			3.34	94.3		83.83	111.67		
LFB-F			0.5	92.0		90	110		
LFB-F			0.5	106.0		90	110		
LFB-F			0.5	106.0		90	110		
MB-F		<0.1							
MB-F		<0.1							
MB-F		<0.1							
MS/MSD	94525004		0.5	70.0	100.0	80	120	7.6	20
MS/MSD	94620005		0.5	102.0	110.0	80	120	2.8	20

Total Dissolved Solids				Units: mg/L					
QC Type	Original Sample ID	Blank Result	Spike Amount	Spike % Recovery	Spike Duplicate % Recovery	Lower Control Limit (%)	Upper Control Limit (%)	RPD (%)	RPD Limit (%)
CRM			736	98.0		90.35	110.33		
CRM			736	99.0		90.35	110.33		
CRM			736	98.0		90.35	110.33		
MB		<10							
MB		<10							
MB		<10							
DUP	94445003							0.5	20
DUP	94620004							1.0	20
DUP	94639004							1.9	20
DUP	94639014							0.0	20
DUP	94639019							2.5	20

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 15 of 18



MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com



Account #: 2040

Client: Basin Electric Power Cooperative



Minnesota Valley Testing Laboratories, Inc.
2616 East Broadway Avenue
Bismarck, ND 58501

Phone: (701) 258-9720

Toll Free: (800) 279-6885

Fax: (701) 258-9724

Basin Electric Power Cooperative

WO: 94620



Chain of Custody

Page 1 of 2

Order #

Company Name and Address		Account #	Phone #
Basin Electric Power Cooperative Leland Olds Station 3901 Highway 200A Stanton, ND 58571		2040	701-745-7238 701-557-5488
Billing Address (indicate if different from above)		Contact	Emails
Attn: Liabilities		Mark Dihle	mdihle@becp.com aknutson@becp.com
		Name of Sampler	
		Mariah Knutson	
		Quote Number	Date Submitted
			8/5/2025
		Project Name/Number	Purchase Order #
		LOS CCR Wells	790708-04

Lab Use Only	Sample ID	Sample Matrix	Date Sampled	Time Sampled	Test	Filtered	Analysis Required
001	MW-2017-1	GW	8/4/2025	813	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
002	MW-2017-2	GW	8/4/2025	900	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
003	MW-2017-3	GW	8/4/2025	928	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
004	MW-2017-4	GW	8/4/2025	1023	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
005	MW-2017-10	GW	8/4/2025	1103	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
006	MW-2017-11	GW	8/4/2025	1221	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
007	DUP	GW	8/4/2025	1221	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
008	MW-2017-7	GW	8/4/2025	1310	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
009	MW-2017-8	GW	8/4/2025	1349	2	N	B, Ca, Cl, F, SO4, TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH

Transferred by	Date	Time	Received by	Date	Time	Temp	ROI	Therm. #
1. MILLENIUM EXPRESS	8/5/2025	NOON	[Signature]	8/5/25	1319	3.2 C	Y/N	70143
2.							Y/N	

Please submit the top copy with your samples. We will return the completed original with your results.

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

**MINNESOTA VALLEY TESTING LABORATORIES, INC.**

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVTL.com

Member
ACIL

Account #: 2040**Client:** Basin Electric Power Cooperative

Minnesota Valley Testing Laboratories, Inc.
2616 East Broadway Avenue
Bismarck, ND 58501
Phone: (701) 258-9720
Toll Free: (800) 279-6885 Fax: (701) 258-9724

Chain of CustodyPage 2 of 2**Work Order #**

Lab Use Only

Company Name and Address Basin Electric Power Coop. Leland Olds Station 3901 Highway 200A Stanton, ND 58571		Account # 2040	Phone # 701-745-7239 701-557-5488
Billing Address (Indicate if different from above) Attn: Liabilities		Contact Mark Dille	Emails mdille@bepc.com aknutson@bepc.com
		Name of Sampler Mariah Knutson	
		Quote Number	Date Submitted 9/18/2024
		Project Name/Number ND0025232	Purchase Order # 790708-04

Lab Use Only	Sample ID	Sample Matrix GW - Groundwater	Date Sampled	Time Sampled	# of Filtered	Analysis Required
Lab						B, Ca, Cl, F, SO ₄ , TDS, Mg, Na, K, Total Alkalinity, (Carbonate, Bicarbonate), pH
010	MW-2017-8D	GW	8/5/2025	805	2 N	

Comments:

Transferred by	Date	Time	Received by	Date	Time	Temp	ROI	Therm. #
1. MILLENNIUM EXPRESS	8/5/2025	NOON	<i>[Signature]</i>	5/19/25	1519	3.2°C	Y/N	1119.5
2.							Y/N	

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 17 of 18



MINNESOTA VALLEY TESTING LABORATORIES, INC.

1126 North Front St. ~ New Ulm, MN 56073 ~ 800-782-3557 ~ Fax 507-359-2890
2616 East Broadway Ave. ~ Bismarck, ND 58501 ~ 800-279-6885 ~ Fax 701-258-9724
1201 Lincoln Hwy. ~ Nevada, IA 50201 ~ 515-382-5486 ~ Fax 515-382-3885
www.MVT.com



Account #: 2040

Client: Basin Electric Power Cooperative



Sample Condition Checklist

Date: 5 Aug 25 Time: 1631 Analyst: RW

Work Order #: 94620

Containers Supplied by MVT: ☒ Yes ☐ No (Designate customer supplied containers as "Other" in container size column)

Comments:											
Number of Bottles	Container Size (mL)			Container Type		Preservation	pH	Sample IDs Preservation reagent added Date/Time Analyst	Unique ID of preservation reagent added	Sample pH after preservation	Required for HNO ₃ samples only (24 hours later) Sample ID pH Recheck Result Date/Time/Analyst
	F-(500) = Filtered			CG = Clear Glass, P = Plastic, AG = Amber Glass							
10	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
10	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	(125) (250) (500) F-(500) (1000)	Other	(CG) (P) (AG)	Other	NONE HNO ₃ H ₂ SO ₄ NaOH NaOH/ZnAcet HCl	<2 >12					
	Oil and grease		(CG) (P) (AG)	Other	HCl	n/a					
	TOC Vials		(G) (AG)		H ₃ PO ₄	n/a					
	DOC Vials		(G) (AG)		None H ₃ PO ₄	n/a					

*All samples requiring analyses performed outside of the Bismarck laboratory (New Ulm and Sub-Contract) are not documented on this form.
*All samples requiring microbiological tests are not documented on this form.

Form #80-910025-2

M:\Documents\FORMS\Approved Templates\Bismarck\Waters\80-910025-2 Sample Condition Checklist
Page 1 of 1

Effective Date : 1 July 2024

MVTL guarantees the accuracy of the analysis done on the sample submitted for testing. It is not possible for MVTL to guarantee that a test result obtained on a particular sample will be the same on any other sample unless all conditions affecting the sample are the same, including sampling by MVTL. As a mutual protection to clients, the public and ourselves, all reports are submitted as the confidential property of clients, and authorization for publication of statements, conclusions or extracts from or regarding our reports is reserved pending our written approval.

Report Date: Tuesday, August 12, 2025 3:24:45 PM

Page 18 of 18



Appendix B

Groundwater Flow Rate

Appendix B
Groundwater Flow Rate
2025 Annual Monitoring Report
LOS Multiunit CCR Groundwater Compliance

LOS - Multiunit Groundwater Velocity Calculation

Sampling Date	5/6/2025
----------------------	----------

Upgradient: MW-2017-07

Top of Casing Elevation	1698.25	ft amsl
Depth to Water	39.96	ft below TOC
Water Level Elevation	1658.29	ft amsl

Downgradient: MW-2017-02

Top of Casing Elevation	1681.03	ft amsl
Depth to Water	22.91	ft below TOC
Water Level Elevation	1658.12	ft amsl

horizontal hydraulic conductivity (Kh)	4.09E-03	cm/s	2023 AGMCAR (AECOM, 2024)
	11.6	ft/day	
porosity (n)	0.33		2023 AGMCAR (AECOM, 2024)
horizontal distance	1630	ft	
WL elevation difference	0.17	ft	
gradient (i)	1.043E-04	ft/ft	
linear velocity (V)	3.66E-03	ft/day	
V	1.3	ft/yr	

Appendix B
Groundwater Flow Rate
2025 Annual Monitoring Report
LOS Multiunit CCR Groundwater Compliance

LOS - Multiunit Groundwater Velocity Calculation

Sampling Date	8/4/2025
----------------------	----------

Upgradient: MW-2017-07

Top of Casing Elevation	1698.25	ft amsl
Depth to Water	39.39	ft below TOC
Water Level Elevation	1658.86	ft amsl

Downgradient: MW-2017-04

Top of Casing Elevation	1684.13	ft amsl
Depth to Water	25.87	ft below TOC
Water Level Elevation	1658.26	ft amsl

horizontal hydraulic conductivity (Kh)	4.09E-03	cm/s	2023 AGMCAR (AECOM, 2024)
	11.6	ft/day	
porosity (n)	0.33		2023 AGMCAR (AECOM, 2024)
horizontal distance	1800	ft	
WL elevation difference	0.60	ft	
gradient (i)	3.333E-04	ft/ft	
linear velocity (V)	1.17E-02	ft/day	
V	4.3	ft/yr	